

**6751W****HANDS-FREE MINI DOOR-ENTRY PHONE. SIMPLEBUS2
(1210A)**

Mini series door-entry phone with full-duplex audio. Allows loudspeaker volume control and ringtone volume control, with choice of different melodies. Equipped with 5 touch sensitive buttons for audio key, lock-release, actuator control, switchboard call and privacy function, with door status indicator LED. Manages floor door calls as standard. Complete with 2 x 8-position dip-switches for programming user code and buttons. Wall-mounted. The door-entry phone can be used in Simplebus2 audio systems with power supply art. 1210. Dimensions: 105x105x20 mm.

AWARDSDESIGN
MILANO



6751W

HANDS-FREE MINI DOOR-ENTRY PHONE. SIMPLEBUS2 (1210A)

Width (mm)	105
Height (mm)	105
Depth (mm)	20
Product weight (g)	150
Product color	White
Wall-mounted	Yes
Audio/video system	Yes

ELECTRICAL CHARACTERISTICS

Supply voltage	22÷35VDC
----------------	----------

HARDWARE FEATURES

Clamps	L L CFP1 CFP2
Removable terminals	Yes
Total buttons (n°)	5
LED signaling (no.) (n°)	3

ENVIRONMENTAL AND COMPLIANCE FEATURES

Operating temperature (°C)	-5 ÷ 40
Operating humidity (RH max) (%)	25 ÷ 75

GENERAL FEATURES

Absorption during communication (mA)	130
Call to multiple addresses	Yes
Selective intercom call	Yes
Panic call	Yes
Doctor	Yes
Switchboard call function	Yes
Floor door call function	Yes
Actuator control function	Yes



6751W

HANDS-FREE MINI DOOR-ENTRY PHONE. SIMPLEBUS2 (1210A)

Intercom function	Yes
Privacy function	Yes
Key button function	Yes
Hands-free function	Yes
Loudspeaker volume control	Yes
Ringtone volume control	Yes
Simplebus 2 audio system	Yes
Electronic bell	Yes
Customisable ringtone	Yes
Sensitive Touch technology	Yes



6751W

HANDS-FREE MINI DOOR-ENTRY PHONE. SIMPLEBUS2 (1210A)



6754 Adapter plate for Mini Handsfree audio

Adapter plate for hands-free Mini audio door-entry phone.