

**IPKCAMA04ZC****VANDALDOME IP CAMERA 4MP 2.8-12MM****ADVANCE
SERIE**

Advance series vandaldome IP camera with IK10 protection rating. Ideal for all installations in which the camera is in a position at risk of tampering or damage. 2.8-12 mm motorised lens with autofocus function, resolution 4MP@30 ips. IR LEDs with a range of 50 metres (SMART IR), ONVIF compatible (Profile S and Profile G). The high frame function (60 fps) is only supported by 32/64/128 ch Advance series NVRs. Video analysis functions: Scene change detection, Object abandoned/removed function, heat map, Face detection, Video tamper detection, Line cross detection (distinction between humans / vehicles), Detection of Entry into / Exit from / Intrusion into an area (distinction between humans / vehicles), Human / vehicle counting on a line and in an area, Metadata analysis, No parking, Loitering, Audio fault. WDR 120Db, compression H.265+/H.265/H.264+/H.264/MJPEG, SD slot (max. 256GB). Audio: 1 in, 1 out, built-in microphone. Alarms: 1 in, 1 out. IP67 waterproof die-cast aluminium enclosure, power supply 12 VDC / PoE IEEE802.3af. Compatible with browsers: IE/Google Chrome/Edge/Firefox/Safari. Compatible accessories: JBA-KA, CMA-KTBBA, WMA-KTBBA, PMA-A, AMA-A, CMA-KCAMA.

AWARDS



IPKCAMA04ZC

VANDALDOME IP CAMERA 4MP 2.8-12MM

MAIN FEATURES

Camera sensor	1/3" CMOS Ultra Starlight
Lens type	Motorized
Lens optical varifocal dimensions (mm)	2.8 ÷ 12
Horizontal FoV (°)	102.7÷32.2
Vertical FoV (°)	57.22÷18.15 (± 5%)
Diagonal FoV (°)	102÷33.9
Electronic shutter (s)	1/25÷100000
Sensitivity (lux)	0.005 (colour), 0 (B/W, led IR ON)
Signal/noise ratio (dB)	>50 (AGC OFF)
IR filter	Mechanical
Video trasmission	Triple streaming
Management software	Comelit CCTV Manager
Video resolution	2592x1520 (4MP)
Tera Operations Per Second (TOPS)	1.5

DORI

Detection (min - max) (m)	58 ÷ 205
Observation (min - max) (m)	23 ÷ 82
Recognition (min - max) (m)	11 ÷ 41
Identification (min - max) (m)	5 ÷ 20

SOFTWARE/FIRMWARE SPECIFICATIONS

Video compression	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Audio compression	G711A/U
Frame rate	30/60fps
Bit rate range (Mbit/s)	0.06 ÷ 8
Protocols supported	DDNS, DHCP, FTP, HTTP, HTTPS, IPv4, IPv6, NTP, PPPoE, QoS, RTCP, RTP, RTSP, SMTP, UDP, UPnP, P2P, SNMP, IEEE 802.1x, RTMP, ONVIF (Profile-S), ONVIF (Profile-G), ONVIF (Profile-M), ONVIF (Profile-T)



IPKCAMA04ZC

VANDALDOME IP CAMERA 4MP 2.8-12MM

SOFTWARE/FIRMWARE SPECIFICATIONS

Updating firmware using network	Yes
Number of simultaneous connections	10 (live)
Network security	Multi-user authorization, HTTPS, AES encryption, RTSP verif.
Remote viewer from browser	Edge, Firefox, Chrome, Safari
Remote control by mobile	APP Comelit CCTV
Latest firmware version	5.1.3.1(52255)(2023-11-08)

FUNCTIONS

Motion detection	Yes
Video analytics	Scene change detection, Face detection, Video tampering detection, Line crossing detection (human / vehicle classification), Region entrance / exit / intrusion detection (human / vehicle classification), Object abandoned / missing detection, Vehicles / people counting, Heat map, metadata-analysis, parking-prohibited, loitering, Audio anomaly
Optimal people detection distance (m)	20
Optimal vehicle detection distance (m)	25
Privacy zones (n°)	4
Back light compensation (BLC)	BLC, HLC
Digital effects	Mirror (Horizontal, Vertical, 180° rotation), ROI zones, Saturation, Brightness, Contrast, Sharpness, Image flip
Wide Dinamic Range (WDR)	WDR (120dB)
Enhanced DNR control	3D-DNR
White balance control	Automatic, Indoor, Manual, Outdoor
Display brightness control	Yes
Image flip	Yes
Automatic gain control (AGC)	Yes
Camera titling	Yes

HARDWARE SPECIFICATIONS

IR LED lighting distance	3 led arrays / 30m (Smart IR)
--------------------------	-------------------------------



IPKCAMA04ZC

VANDALDOME IP CAMERA 4MP 2.8-12MM

HARDWARE SPECIFICATIONS

IK vandal-resistance rating (with product installed)	IK10
IP protection rating (with product installed)	IP67
Alarm Inputs/Outputs	1/1
Maximum load alarm outputs	24 V DC/AC 1A
Audio Inputs/Outputs	1 + Mic / 1
Analogue video output	CVBS (BNC)
LAN output type	Ethernet 10/100 Mbit/s (RJ45)
Support SD card (card not included)	Micro-SD (256GB max)

GENERAL DATA

Supply voltage	12VDC
Max absorption (W)	10.5
PoE power supply	Standard IEEE 802.3af
Type of power supply	PoE, External power supply
Diameter (mm)	141
Height (mm)	100
Product weight (g)	930
Type of finishing materials	Die-cast aluminum, High Impact Polycarbonate
Product color	White
Operating temperature (°C)	-30 ÷ 60
Operating humidity (RH max) (%)	25 ÷ 95

**IPKCAMA04ZC****VANDALDOME IP CAMERA 4MP 2.8-12MM****ACCESSORIES****CMA-
KCAMA****FLUSH-MOUNT CEILING BACKPLATE, ADVANCE VANDALDOME**

This accessory is used for flush mounting Advance series vandaldome cameras, making them more discreet and less exposed to tampering attempts. For model compatibility please refer to the diagram in the download section.

**WMA-
KTBBA****ADVANCE NEXT WALL BACKPLATE**

Wall-mounting bracket for Next and Advance cameras. For model compatibility please refer to the diagram in the download section.

**CMA-
KTBBA****ADVANCE NEXT CEILING BACKPLATE**

Ceiling-mounting accessory for Next and Advance cameras. For model compatibility please refer to the diagram in the download section.

**PMA-A****ADVANCE ADVANCE NEXT BEUGEL OP PAAL POLE-MOUNTING BACKPLATE**

Pole-mounting accessory for Next and Advance cameras. For model compatibility please refer to the diagram in the download section. Pole diameter from 80 to 140 mm

**JBA-KA****ADVANCE NEXT CONNECTION BOX IP66**

Junction box for securing Next and Advance cameras. For model compatibility please refer to the diagram in the download section.

**AMA-A****ADVANCE NEXT CORNER BACKPLATE**

Corner-mounting accessory for Next and Advance cameras. For model compatibility please refer to the diagram in the download section.